

GATORBAR®

APPLICATION DATA SHEET

**ZERO SLIVERS.
BETTER BOND.**



ICC AC454 CERTIFIED (ESR-4526)
GatorBar #3 only (#4 & #5 pending)



An ACI Center of Excellence for
Nonmetallic Building Materials
MEMBERSHIP



PHYSICAL PROPERTIES

	#3 BAR	#4 BAR	#5 BAR
Nominal Diameter	10 mm 3/8 in	13 mm 1/2 in	16 mm 5/8 in
Weight	.09 lbs/ft (1.8 lbs/stick) >75% Fiber Content	.166 lbs/ft (3.32 lbs/stick) >75% Fiber Content	.2475 lbs/ft (4.95 lbs/stick) >75% Fiber Content
Guaranteed Tensile Strength ASTM 7205	1100 MPa 155 ksi 17,100 lbs	1100 MPa 155 ksi 30,400 lbs	889 MPa 129 ksi 39,750 lbs
Tensile Modulus of Elasticity ASTM 7205	47 GPa 6.8 x 10 ⁶ psi	49 GPa 7.1 x 10 ⁶ psi	44.7 GPa 6.5 x 10 ⁶ psi
Guaranteed Transverse Shear Capacity ASTM 7617	185 MPa 26.8 ksi 6,800 lbs	185 MPa 26.8 ksi 10,500 lbs	185 MPa 26.8 ksi 16,800 lbs
ICC-ESR	AC454 Certified (ESR-4526) for #3 (#4 & #5 pending)		
Bond Strength ASTM D7913	1100 psi guaranteed for #3 (#4 & #5 pending)		
Moisture Content ASTM D570	< 0.25% (#3, #4, & #5)		

Performance Standards

Above performance criteria are met or exceeded in accordance with ASTM D7957, ASTM D7913, ACI440.11, and AC454

PRODUCT FEATURES

LOWER COSTS 35% - 45% LABOR SAVINGS	ZERO SLIVERS GRIP TECH FOR BETTER HANDLING
2X STRONGER THAN STEEL	4X LIGHTER THAN STEEL
RUST FREE LONGER LASTING CONCRETE	BETTER BOND INCREASED PULL- OUT STRENGTH

APPLICATIONS

- ✓ PAVEMENTS
- ✓ COMMERCIAL FLOORS
- ✓ PARKING LOTS
- ✓ POURED WALLS
- ✓ CURB & GUTTER
- ✓ FOUNDATIONS & FOOTINGS
- ✓ SIDEWALKS
- ✓ AND MANY MORE!

**HUNDREDS OF MILLIONS
OF FEET IN CONCRETE**



AMERICA'S REBAR

PATENT #9688030B2

ZERO POLYESTER

906.934.2661

GATORBAR.COM



GATORBAR® VS STEEL

TENSILE STRENGTH & WEIGHT COMPARISONS*

STEEL REBAR (GRADE 60)	#3 GATORBAR		#4 GATORBAR		#5 GATORBAR	
	STRONGER	LIGHTER	STRONGER	LIGHTER	STRONGER	LIGHTER
#3 STEEL	2.7X	4X	4.4X	2.3X	6.2X	1.2X
#4 STEEL	1.5X	7.4X	2.5X	4X	3.5X	2.7X
#5 STEEL	CALL FOR ENGINEERING ASSISTANCE		1.6X	6.3X	2.1X	4.2X
#6 STEEL	CALL FOR ENGINEERING ASSISTANCE: 906.934.2661				1.5X	6X

*FOR CRACK CONTROL CONSIDERATION. IT IS NOT GATORBAR'S INTENT TO IMPLY THAT COMPOSITE REBAR CAN REPLACE STEEL IN ALL APPLICATIONS.



BUST BAR. NOT YOUR BACK.



DRIVE ON. DRIVE OFF.



SPACING RECOMMENDATIONS

GATORBAR'S DESIGN AND INSTALLATION MANUAL RECOMMENDS:

4" CONCRETE	24" TO 30" WITH #3 GATORBAR
6" CONCRETE	18" TO 24" WITH #3 GATORBAR 24" TO 30" WITH #4 GATORBAR
8" CONCRETE	12" TO 18" WITH #3 GATORBAR 18" TO 24" WITH #4 GATORBAR