



PHYSICAL PROPERTIES

	#3 BAR	#4 BAR
NOMINAL DIAMETER/AREA	10 mm 3/8 in	13 mm 1/2 in
WEIGHT	.09 lbs/ft (1.8 lbs/stick) >75% Fiber Content	.166 lbs/ft (3.32 lbs/stick) >75% Fiber Content
GUARANTEED TENSILE STRENGTH ASTM 7205	1100 MPa 160 ksi 17,600 lbs	1100 MPa 160 ksi 31,000 lbs
TENSILE MODULUS OF ELASTICITY ASTM 7205	46 GPa 6.7 x 10 ⁶ psi	
GUARANTEED TRANSVERSE SHEAR CAPACITY ASTM 7617	151 MPa 22 ksi 2,400 lbs	151 MPa 22 ksi 4,300 lbs
MOISTURE CONTENT ASTM D570	< 0.25%	

72k BUSHEL BIN

- ✓ 75 yards concrete
- ✓ 156 sticks #3 GatorBar
24" centers



PRODUCT FEATURES

LOW COST → BEAT STEEL ON PRICE

HIGH STRENGTH → STRONGER THAN STEEL

LIGHTWEIGHT → LABOR AND FREIGHT SAVINGS

RUST-FREE → WILL NOT CORRODE IN HIGH CHLORIDE APPLICATIONS

REDUCED INJURY → LIGHTER THAN STEEL= LESS LIFTING INJURIES

 **100% MADE IN THE USA**

NO POLYESTER | PATENT #9688030B2

FASTER INSTALL. BETTER CONCRETE.

906.934.2661 | GATORBAR.COM